

## Plastové trubky

### **FX** Plastová trubka ohybná, samozhášavá 320N

Farba svetlo šedá RAL 7035

Symbol výrobku	dn mm	di mm	dĺžka m	tepl. rozsah °C
<b>FX</b>				
FX 16	16,0	12,1	50	-5°C/+60°C
FX 20	20,0	15,0	50	-5°C/+60°C
FX 25	25,0	19,1	50	-5°C/+60°C
FX 32	32,0	26,3	25	-5°C/+60°C
FX 40	40,0	33,8	25	-5°C/+60°C
FX 50	50,0	43,5	25	-5°C/+60°C
FX 63	63,0	55,7	25	-5°C/+60°C

Voliteľné príslušenstvo:

- SM** Spojka trubky
- SB** Kolená trubky
- CL** Príchytky trubky

V zhode s EN 50086-2-2, IEC 61386-22,  
IEC 60614-2-3 (predtým BS 6099)



### **FXP-Turbo** Plastová trubka ohybná pancierová, samozhášavá 750N , silikon FREE

Farba šedá RAL 7037

Symbol výrobku	dn mm	di mm	dĺžka m	tepl. rozsah °C
<b>FXP-Turbo</b>				
FXP-Turbo 16	16,0	10,9	50	-25°C/+60°C
FXP-Turbo 20	20,0	14,5	50	-25°C/+60°C
FXP-Turbo 25	25,0	18,8	50	-25°C/+60°C
FXP-Turbo 32	32,0	24,4	25	-25°C/+60°C
FXP-Turbo 40	40,0	30,9	25	-25°C/+60°C
FXP-Turbo 50	50,0	39,4	25	-25°C/+60°C
FXP-Turbo 63	63,0	52,2	25	-25°C/+60°C

Voliteľné príslušenstvo:

- SM GR** Spojka trubky
- SB GR** Kolená trubky
- CL GR** Príchytky trubky

V zhode s EN 50086-2-2, IEC 61386-22,  
IEC 60614-2-3 (predtým BS 6099)



## Plastové trubky

### **VRM-Turbo** Plastová trubka pevná s hrdlom, samozhášavá 320N

Farba svetlo šedá RAL 7035

Symbol výrobku	dn mm	di mm	dĺžka m	tepl. rozsah °C
<b>VRM-Turbo</b>				
VRM-Turbo 16	16,0	13,7	111	-5°C/+60°C
VRM-Turbo 20	20,0	17,5	111	-5°C/+60°C
VRM-Turbo 25	25,0	22,3	57	-5°C/+60°C
VRM-Turbo 32	32,0	29,1	57	-5°C/+60°C
VRM-Turbo 40	40,0	35,5	21	-5°C/+60°C
VRM-Turbo 50	50,0	44,8	21	-5°C/+60°C

Voliteľné príslušenstvo:

- SM** Spojka trubky
- SB** Kolená trubky
- CL** Príchytky trubky

V zhode s IEC 61386-21, IEC60423,  
IEC 60614-2-2 (predtým BS 6099)



### **UPRM-Turbo** Plastová trubka pevná pancierová s hrdlom, samozhášavá 750N

Farba šedá RAL 7037

Symbol výrobku	dn mm	di mm	dĺžka m	tepl. rozsah °C
<b>UPRM-Turbo</b>				
UPRM-Turbo 16	16,0	13,0	111	-25°C/+60°C
UPRM-Turbo 20	20,0	16,9	111	-25°C/+60°C
UPRM-Turbo 25	25,0	21,4	57	-25°C/+60°C
UPRM-Turbo 32	32,0	27,8	57	-25°C/+60°C
UPRM-Turbo 40	40,0	35,4	21	-25°C/+60°C
UPRM-Turbo 50	50,0	44,3	21	-25°C/+60°C
UPRM-Turbo 63	63,0	54,0	21	-25°C/+60°C

Voliteľné príslušenstvo:

- SM GR** Spojka trubky
- SB GR** Kolená trubky
- CL GR** Príchytky trubky

V zhode s IEC 61386-21, IEC60423,  
IEC 60614-2-3 (predtým BS 6099)



## Plastové trubky - príslušenstvo

### CL Plastová príchytky (KLIP), samozhášavá

Farba svetlo šedá RAL 7035, šedá (GR) RAL 7037, čierna RAL 9005, biela RAL 9010

Symbol výrobku	dn mm	balenie ks	tepl. rozsah °C
<b>CL</b>			
CL 16	16,0	100	-5°C/+60°C
CL 16 GR	16,0	100	-25°C/+60°C
CL 20	20,0	100	-5°C/+60°C
CL 20 GR	20,0	100	-25°C/+60°C
CL 25	25,0	100	-5°C/+60°C
CL 25 GR	25,0	100	-25°C/+60°C
CL 32	32,0	100	-5°C/+60°C
CL 32 GR	32,0	100	-25°C/+60°C
CL 40	40,0	50	-5°C/+60°C
CL 40 GR	40,0	50	-25°C/+60°C
CL 50	50,0	50	-5°C/+60°C
CL 50 GR	50,0	50	-25°C/+60°C
CL 63	63,0	50	-5°C/+60°C
CL 63 GR	63,0	50	-25°C/+60°C

Voliteľné príslušenstvo:

**DSD** Plastová hmoždinka

... Skrutka Ø 4 mm



### CLB Plastová spona na príchytky (KLIP), samozhášavá

Farba svetlo šedá RAL 7035, šedá (GR) RAL 7037, čierna RAL 9005

Symbol výrobku	dn mm	balenie ks	tepl. rozsah °C
<b>CLB</b>			
CLB 40	40,0	250	-5°C/+60°C
CLB 40 GR	40,0	250	-25°C/+60°C
CLB 50	50,0	200	-5°C/+60°C
CLB 50 GR	50,0	200	-25°C/+60°C
CLB 63	63,0	150	-5°C/+60°C
CLB 63 GR	63,0	150	-25°C/+60°C



### DSD Plastová samonosná hmoždinka, samozhášavá

Farba svetlo šedá RAL 7035

Symbol výrobku	Ø mm	hĺbka otvoru mm	balenie ks	tepl. rozsah °C
<b>DSD</b>				
DSD 35	6 (5,5)	35,0	500	-25°C/+90°C

